

Tbi CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 1 of 14

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Tbi CeraProtect 400ml (392P000070)

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricants, greases, release products
Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name:	Tbi Industries GmbH	
Street:	Robert-Bosch-Str.20	
Place:	D-61184 Karben	
Telephone:	+ 49 6039 9292-0	Telefax: + 49 6039 9292-058
E-mail:	info@tbi-industries.com	
Internet:	www.tbi-industries.com	

1.4. Emergency telephone number: +49 (0) 551 19240 poison centre - north, 24h**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aerosol 1; H222-H229
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Acetone

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P280	Wear protective gloves and eye/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

TBi CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 2 of 14

P337+P313

If eye irritation persists: Get medical advice/attention.

P410+P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

Even after use and until complete evaporation of the flammable components, there is still a danger of an explosive steam-air mixture forming.

SECTION 3: Composition/information on ingredients
3.2. Mixtures
Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
115-10-6	Dimethyl ether			75 - < 80 %
	204-065-8	603-019-00-8	01-2119472128-37	
	Flam. Gas 1, Liquefied gas; H220 H280			
67-64-1	Acetone			12.5 - < 15 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
109-87-5	Dimethoxymethane			0.5 - < 1 %
	203-714-2		01-2119664781-31	
	Flam. Liq. 2; H225			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
115-10-6	204-065-8	Dimethyl ether	75 - < 80 %
		inhalation: LC50 = 164000 ppm (gases)	
67-64-1	200-662-2	Acetone	12.5 - < 15 %
		inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = > 7426 mg/kg; oral: LD50 = 5800 mg/kg	
109-87-5	203-714-2	Dimethoxymethane	0.5 - < 1 %
		dermal: LD50 = > 5000 mg/kg; oral: LD50 = 6423 mg/kg	

SECTION 4: First aid measures
4.1. Description of first aid measures
General information

When in doubt or if symptoms are observed, get medical advice. If medical advice is needed, have product container or label at hand.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse. In case of skin irritation, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 3 of 14

(only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Remove persons to safety. Ventilate affected area. Do not breathe aerosol.

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up**For cleaning up**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 4 of 14

temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities
Requirements for storage rooms and vessels

Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Lubricants, greases, release products

SECTION 8: Exposure controls/personal protection
8.1. Control parameters
Occupational exposure limit values

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
115-10-6	Dimethylether	1000	1920		TWA (8 h)	

TBi CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 5 of 14

DNEL/DMEL values

CAS No	Name of agent		
DNEL type	Exposure route	Effect	Value
115-10-6	Dimethyl ether		
Consumer DNEL, long-term	inhalation	systemic	471 mg/m ³
Worker DNEL, long-term	inhalation	systemic	1894 mg/m ³
67-64-1	Acetone		
Worker DNEL, long-term	inhalation	systemic	1210 mg/m ³
Worker DNEL, acute	inhalation	local	2420 mg/m ³
Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	200 mg/m ³
Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day
109-87-5	Dimethoxymethane		
Worker DNEL, long-term	inhalation	systemic	126,6 mg/m ³
Worker DNEL, long-term	dermal	systemic	17,9 mg/kg bw/day
Consumer DNEL, long-term	inhalation	systemic	31,5 mg/m ³
Consumer DNEL, long-term	dermal	systemic	18,1 mg/kg bw/day
Consumer DNEL, long-term	oral	systemic	18,1 mg/kg bw/day

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 6 of 14

PNEC values

CAS No	Name of agent		Value
Environmental compartment			
115-10-6	Dimethyl ether		
Freshwater			0,155 mg/l
Freshwater (intermittent releases)			1,549 mg/l
Marine water			0,016 mg/l
Freshwater sediment			0,681 mg/kg
Marine sediment			0,069 mg/kg
Micro-organisms in sewage treatment plants (STP)			160 mg/l
Soil			0,045 mg/kg
67-64-1	Acetone		
Freshwater			10,6 mg/l
Freshwater (intermittent releases)			21 mg/l
Marine water			1,06 mg/l
Freshwater sediment			30,4 mg/kg
Marine sediment			3,04 mg/kg
Micro-organisms in sewage treatment plants (STP)			100 mg/l
Soil			29,5 mg/kg
109-87-5	Dimethoxymethane		
Freshwater			14,577 mg/l
Marine water			1,477 mg/l
Freshwater sediment			13,135 mg/kg
Micro-organisms in sewage treatment plants (STP)			10000 mg/l
Soil			4,654 mg/kg

8.2. Exposure controls
Appropriate engineering controls

Do not breathe gas/fumes/vapour/spray. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Individual protection measures, such as personal protective equipment
Eye/face protection

Wear eye/face protection. Suitable eye protection: goggles. EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: Butyl caoutchouc (butyl rubber) EN ISO 374

Thickness of the glove material: 0,6 mm

Breakthrough time: > 480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus:

Combination filtering device A-P2

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 7 of 14

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	white
Odour:	like: Solvent

Test method

Melting point/freezing point:	not determined
Boiling point or initial boiling point and boiling range:	< -20 °C
Flammability:	not determined
Lower explosion limits:	2,15 vol. %
Upper explosion limits:	26,2 vol. %
Flash point:	< -20 °C
Auto-ignition temperature:	226 °C
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not applicable
Water solubility: (at 20 °C)	slightly soluble
Solubility in other solvents not determined	
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Vapour pressure: (at 55 °C)	10.500 hPa FEA 604
Density (at 20 °C):	0,697 g/cm ³ calculated.
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information
Information with regard to physical hazard classes
Explosive properties

Heating may cause an explosion.

Oxidizing properties

The product is not: oxidising.

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined

SECTION 10: Stability and reactivity
10.1. Reactivity

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 8 of 14

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008
Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
115-10-6	Dimethyl ether				
	inhalation (4 h) gas	LC50 ppm	164000	Rat	Study report (1979) Ten male rats were administered the test
67-64-1	Acetone				
	oral	LD50 mg/kg	5800	Rat	J Toxicol Environ Health 15: 609-621 (19)
	dermal	LD50 mg/kg	> 7426	Rabbit	Toxicol Appl Pharmacol 7: 559-565. (1965) other: Code of federal regulations: 21 C
	inhalation (4 h) vapour	LC50	76 mg/l	Rat	
109-87-5	Dimethoxymethane				
	oral	LD50 mg/kg	6423	Rat	Study report (1982) OECD Guideline 423
	dermal	LD50 mg/kg	> 5000	Rabbit	Study report (1989) OECD Guideline 402

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Acetone)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 9 of 14

Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. No further relevant information available.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 10 of 14

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
115-10-6	Dimethyl ether					
	Acute fish toxicity	LC50 mg/l	> 4100	96 h	Poecilia reticulata	Study report (1988) other: NEN 6504 Water - Determination of
	Acute algae toxicity	ErC50 mg/l	154,917	96 h	green algae	Other company data (2009) other: Data generated using ECOSAR v1.00
	Acute crustacea toxicity	EC50 mg/l	> 4400	48 h		Study report (1988) other: NEN6501: Water -Determination of
67-64-1	Acetone					
	Acute fish toxicity	LC50 mg/l	8120	96 h		Publication (1984) OECD Guideline 203
	Acute crustacea toxicity	EC50 mg/l	8800	48 h	Daphnia pulex	Publication (1978) The toxicity of acetone towards daphnids
	Algae toxicity	NOEC	430 mg/l	4 d		
	Crustacea toxicity	NOEC mg/l	2212	28 d		Arch Environm Contam Toxicol 12: 305-310 Study conducted comparable to OECD 211 w
	Acute bacteria toxicity	(EC50 mg/l)	61150	0,5 h	activated sludge of a predominantly domestic sewage	Water Res 26: 887-892 (1992) ISO 8192
109-87-5	Dimethoxymethane					
	Acute fish toxicity	LC50 mg/l	> 1000	96 h	Danio rerio	Study report (1991) OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	9120	72 h	Raphidocelis subcapitata	Study report (2015) other: REACH guidance on QSAR R6, May 20
	Acute crustacea toxicity	EC50 mg/l	> 1200	48 h		Study report (1991) OECD Guideline 202
	Fish toxicity	NOEC mg/l	450,281	30 d	not relevant	Study report (2012) other: REACH guidance on QSAR R6, May 20
	Algae toxicity	NOEC mg/l	145,77	30 d	algae	Study report (2012) other: REACH guidance on QSAR R6, May 20
	Crustacea toxicity	NOEC mg/l	150,5	30 d		Study report (2012) other: REACH guidance on QSAR R6, May 20

12.2. Persistence and degradability

The product has not been tested.

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 11 of 14

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-64-1	Acetone			
	Biodegradation	91%	28	
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
115-10-6	Dimethyl ether	0,07
67-64-1	Acetone	-0,23
109-87-5	Dimethoxymethane	0

BCF

CAS No	Chemical name	BCF	Species	Source
67-64-1	Acetone	3		Unpublished calculat
109-87-5	Dimethoxymethane	0,6		REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations
13.1. Waste treatment methods
Disposal recommendations

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Completely emptied packages can be recycled.

SECTION 14: Transport information
Land transport (ADR/RID)

14.1. UN number or ID number:	UN 1950
14.2. UN proper shipping name:	AEROSOLS
14.3. Transport hazard class(es):	2
14.4. Packing group:	-
Hazard label:	2.1

Tbi CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 12 of 14



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: 63 190 277 327 344 381 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 13 of 14

IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40

2010/75/EU (VOC): 94,552 % (659,027 g/l)

2004/42/EC (VOC): 94,552 % (659,027 g/l)

Information according to 2012/18/EU (SEVESO III): P3a FLAMMABLE AEROSOLS

Additional informationTo follow: 850/2004/EC, 79/117/EEC, 689/2008/EC, 2008/47/EC
Aerosol Directive (75/324/).**National regulatory information**

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 4,5,6,7,8,9,11,12,14,16.

Abbreviations and acronymsADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

TBI CeraProtect 400ml (392P000070)

Revision date: 05.07.2023

Page 14 of 14

LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Eye Irrit. 2; H319	Bridging principle "Aerosols"
STOT SE 3; H336	Bridging principle "Aerosols"

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)